



## PRODUCTS FOR LUBRICATION

# **FAG CONCEPT2**

FAG CONCEPT2 – one device that replaces two devices for individual lubrication



#### Product features

- Up to two outlets with independently adjustable lubrication intervals
- Power supply: 24 V DC or battery
- Lubricating media: Oil and grease up to NLGI 2
- Lubricant reservoir: 250 cm<sup>3</sup> cartridge
- Delivery pressure: Up to 50 bar (with 24 V DC) or 30 bar (with battery)
- Operating temperature: -20 °C to +70 °C
- Piston pump principle

## **Technical advantages**

- Supply of up to two lubrication points
- Different lubrication intervals for each outlet
- Battery and mains operation possible
- Wide operating temperature range
- Reliable piston pumps as feed pumps
- Metering quantities independent of the ambient temperature
- Measurement of back pressure up to the lubrication point
- · Optional activation using an external control unit
- High pressure build-up
- Monitoring of motor running and filling level

#### **Customer benefits**

- Only one lubricating device is needed instead of two
- Two bearings with different lubrication requirements can be supplied
- Can easily be integrated into machine operation
- The maintenance process is simplified
- Good price/performance ratio

## **Applications**

Ideal for applications with two lubrication points

- Electric motors
- Fans
- Compressors

Also ideal for original equipment and retrofitting



Rolling bearing lubrication with Arcanol and FAG CONCEPT2







# Types available

- FAG CONCEPT2 for one lubrication point with battery or 24 V power supply
- FAG CONCEPT2 for two lubrication points with battery or 24 V power supply

# Schaeffler Technologies AG & Co. KG

Georg-Schäfer-Strasse 30 97421 Schweinfurt Germany Internet www.schaeffler.de/services E-Mail industrial-services@schaeffler.com Every care has been taken to ensure the correctness of the information contained in this publication but no liability can be accepted for any errors or omissions. We reserve the right to make technical changes.

© Schaeffler Technologies AG & Co. KG Issued: 2015, April

This publication or parts thereof may not be reproduced without our permission.